

DISPLAY D1-D2-D3-D4 COMPARISON

	D1	D2	D3	D4
Display	OLED 1.5" 128x64 pixel	TFT 2.41" 320x240 pixel	TFT 5" 800x445 pixel Touch Screen	TFT 7" 800x445 pixel Touch Screen
Keyboard	8 resistors touch keys	5 capacitive touch keys with RGB backlite	6 resistors touch keys	6 resistors touch keys
Ports	Canbus	Canbus - USB - microSD	Canbus - USB - microSD	Canbus - USB - microSD
Clock	no	RTC with capacitor backup	RTC with capacitor backup	RTC with capacitor backup
Power Supply	From controller board	From controller board	From controller board	From controller board
Housing	ABS	ABS	ABS	ABS
Dimensions	185x43x13mm	162x52x30mm	168x100x24mm	215x128x28mm
Drilling Template	150x31mm fixing distance between front screws	154x50mm	154x49.5mm	199x121mm
Display compatibility	TOP FOOD ECO4 - ECO 6	PR02 - PR01 TOP FOOD - ECO4 - ECO 6 EVO 6	PR02 - PR01 TOP FOOD - ECO4 - ECO 6	PR02 - PR01 TOP FOOD - ECO4 - ECO 6
Bridge compatibility	Ethernet - WiFi -3G	Etheret - WiFi -3G - TCP	Ethernet - WiFi -3G - TCP	Ethernet - WiFi -3G - TCP
ORDER CODES				
Flush mounting	BT92104000	BT92101000	BT92102000	BT92103000
Rear mounting	BT92104100	BT92101100	BT92102100	BT92103100